## Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A sound-absorbing structure, comprising:

a substantially flat support base;

a substantially flat sound-absorbing material arranged substantially parallel to the support base; and

a corrugated partition plate interposed between the support base and the soundabsorbing material, the corrugated partition plate having upper antinode portions opposed to the sound-absorbing material and lower antinode portions opposed to the support base;

wherein at least one and less than all of the lower antinode portions is supported by and in contact with an elastic element by low-vibration portions of the support base, and the remaining lower antinode portions of the corrugated partition plate are at least partially separated from the support base by an air gap  $(\Delta)$ .

- 2. (Canceled)
- 3. (Previously Presented) The sound-absorbing structure as claimed in claim 1, wherein the corrugated partition plate has a first side and a second side opposite to the first side; and

wherein the substantially flat sound-absorbing material is provided on the first side of the corrugated partition plate.

- 4. (Previously Presented) The sound-absorbing structure as claimed in claim 16, wherein the second partition plate extends in a direction substantially perpendicular to a direction in which antinode portions of the corrugated partition plate extend.
  - 5. (Canceled)

- 6. (Previously Presented) The sound-absorbing structure as claimed in claim 16, wherein the second partition plate is provided only on the first side of the corrugated partition plate.
- 7. (Previously Presented) The sound-absorbing structure as claimed in claim 16, wherein the corrugated partition plate includes a wave pattern whose phase is shifted at an intersection of the corrugated partition plate and the second partition plate.
- 8. (Previously Presented) The sound-absorbing structure as claimed in claim 16, wherein the corrugated partition plate includes a wave pattern whose amplitude is varied at an intersection of the corrugated partition plate and the second partition plate.
- 9. (Previously Presented) The sound-absorbing structure as claimed in claim 3, wherein the corrugated partition plate includes a sine wave pattern.
- 10. (Previously Presented) The sound-absorbing structure as claimed in claim 3, wherein the corrugated partition plate includes a rectangular wave pattern.
- 11. (Previously Presented) The sound-absorbing structure as claimed in claim 3, wherein the corrugated partition plate includes wave patterns with different frequencies.
- 12. (Previously Presented) The sound-absorbing structure as claimed in claim 3, wherein the corrugated partition plate includes wave patterns with different amplitudes.
  - 13. (Currently Amended) A sound-absorbing unit comprising:a substantially flat support base;
- a partition plate having a plurality of recesses formed in a first side thereof, each of said recesses having an opening with a predetermined shape on the first side; and
- a substantially flat sound-absorbing material arranged substantially parallel to the support base and provided on the first side of the partition plate to cover the openings of the recesses;

wherein the recesses have upper portions opposed to the sound-absorbing material and lower portions opposed to the support base;

wherein each of the recesses has a cross-sectional area that gradually varies with a depth of the recess;

wherein at least one and less than all of the lower portions of the recesses are supported by and in contact with an elastic element by low-vibration portions of the support base, and the remaining lower portions are at least partially separated from the support base by an air gap  $(\Delta)$ .

- 14. (Canceled)
- 15. (Currently Amended) The sound-absorbing structure unit-as claimed in claim 3, wherein the thickness of air spaces behind the sound-absorbing material is set to odd multiples of one-fourth of the wavelength of sound waves of target frequencies.
- 16. (Currently Amended) The sound-absorbing <u>structure unit-as</u> claimed in claim 3, further comprising:

at least one second partition plate configured to partition air spaces defined between the sound-absorbing material and the corrugated partition plate.

17. (New) The sound-absorbing structure as claimed in claim 1, wherein neighboring upper antinode portions of the corrugated partition plate are in contact with the sound-absorbing material.